

FIGURE 2

RESISTANCE VALUES OBTAINABLE

IRC TYPE NO.	# 1 CARBON COATING *		# 2 CARBON COATING		OUR RECOMMENDED MAXIMUM		
	MINIMUM		MAXIMUM				
	STANDARD	ON SPECIAL ORDER	STANDARD	ON SPECIAL ORDER			
BTR	500 OHMS	100 OHMS	26,000 OHMS	65,000 OHMS	20 MEG.	50 MEG.	5 MEG.
BTS	500 "	100 "	26,000 "	65,000 "	20 "	50 "	10 "
BT-½	250 "	50 "	43,000 "	107,500 "	20 "	100 "	20 "
BT-1	350 "	70 "	101,000 "	252,500 "	20 "	100 "	20 "
BT-2	500 "	100 "	175,000 "	437,500 "	20 "	100 "	50 "
BW TYPE							
MINIMUM		MAXIMUM					
STANDARD		STANDARD		ON SPECIAL ORDER		002344	
BW ½	.24 OHMS	800 OHMS	1500 OHMS				
BW-1	.50 "	5000 "	10,000 "				
BW-2	1.0 "	8000 "	15,000 "	PX-1-62		800 OHMS 3000 " 5000 "	

MINN. C.A. 4-67 CIV 138

PLAINTIFF'S TRIAL EXHIBIT No. 21882

* # 1 Carbon coating is preferred by us because of improved ability to stand heat and lower noise level.

