



PIN	FIELD OR CAN	COLOR CODE
1	A	GR. WH.
2	B	BR. WH.
3	C	GR. BR. WH.
4	D	GR. WH.
5	CB-9	BL. WH.
6		
1	E	WH.
2	F	OR. WH.
3	G	Y. WH.
4	H	R. WH.
5	CB-9	BL. WH.
6		

NOTE:

NO WIRES SHOWN ON PX-11-118 HAVE BEEN CHANGED. THE WIRES SHOWN ON THIS DRAWING HAVE BEEN ADDED TO MAKE 12 PUNCH RECEPTION FOR MINUS SIGNS POSSIBLE. THIS WIRING ACCOMMODATES ONLY 8 PMS FOR THE OTHER, 8 THESE CHANGES MUST BE DUPLICATED.

SYM	DESCRIPTION	DATE	APPROVAL

PHYSICAL PROPERTIES	
YP	
TS	
EL 2	
RA	
DH	
HN	

TOLERANCES ON DECIMALS	
ANGLES	FRACTIONS
MATERIAL	
HEAT TREATMENT	
FINAL PROTECTIVE FINISH	

ORIGINAL DATE OF DRAWING	1/2/53
DRAFTSMAN	ALD
CHECKER	JFC
TRACER	
ENGINEER	JFC
SUBMITTED	

ADDITIONAL RELAYS
To ACCOMMODATE
12 PUNCH FOR
MINUS SIGNS

ORDNANCE CORPS
DEPT OF THE ARMY
PX-11-118A

C