



MOORE SCHOOL OF ELECTRICAL ENGINEERING
UNIVERSITY OF PENNSYLVANIA

RACK TOP ANGLE

FINISH: MARBLED BLACK

DATE: 7-26-44

BY: [Signature]

7-26-44

23220

VARIATIONS ON FINISHED DIMENSIONS (UNLESS OTHERWISE SPECIFIED)	
BASIC DIMENSIONS	D
UP TO 3/4"	± 0.005
ABOVE 3/4" TO 1 1/2"	± 0.010
ABOVE 1 1/2" TO 2 1/2"	± 0.015
ABOVE 2 1/2" TO 4"	± 0.020
ABOVE 4" TO 6"	± 0.030
ABOVE 6" TO 12"	± 0.040
ABOVE 12" TO 24"	± 0.050
ABOVE 24" TO 48"	± 0.060
ABOVE 48" TO 96"	± 0.070
ABOVE 96" TO 144"	± 0.080
ABOVE 144" TO 192"	± 0.090
ABOVE 192" TO 240"	± 0.100
ABOVE 240" TO 288"	± 0.110
ABOVE 288" TO 336"	± 0.120
ABOVE 336" TO 384"	± 0.130
ABOVE 384" TO 432"	± 0.140
ABOVE 432" TO 480"	± 0.150
ABOVE 480" TO 528"	± 0.160
ABOVE 528" TO 576"	± 0.170
ABOVE 576" TO 624"	± 0.180
ABOVE 624" TO 672"	± 0.190
ABOVE 672" TO 720"	± 0.200
ABOVE 720" TO 768"	± 0.210
ABOVE 768" TO 816"	± 0.220
ABOVE 816" TO 864"	± 0.230
ABOVE 864" TO 912"	± 0.240
ABOVE 912" TO 960"	± 0.250
ABOVE 960" TO 1008"	± 0.260
ABOVE 1008" TO 1056"	± 0.270
ABOVE 1056" TO 1104"	± 0.280
ABOVE 1104" TO 1152"	± 0.290
ABOVE 1152" TO 1200"	± 0.300
ABOVE 1200" TO 1248"	± 0.310
ABOVE 1248" TO 1296"	± 0.320
ABOVE 1296" TO 1344"	± 0.330
ABOVE 1344" TO 1392"	± 0.340
ABOVE 1392" TO 1440"	± 0.350
ABOVE 1440" TO 1488"	± 0.360
ABOVE 1488" TO 1536"	± 0.370
ABOVE 1536" TO 1584"	± 0.380
ABOVE 1584" TO 1632"	± 0.390
ABOVE 1632" TO 1680"	± 0.400
ABOVE 1680" TO 1728"	± 0.410
ABOVE 1728" TO 1776"	± 0.420
ABOVE 1776" TO 1824"	± 0.430
ABOVE 1824" TO 1872"	± 0.440
ABOVE 1872" TO 1920"	± 0.450
ABOVE 1920" TO 1968"	± 0.460
ABOVE 1968" TO 2016"	± 0.470
ABOVE 2016" TO 2064"	± 0.480
ABOVE 2064" TO 2112"	± 0.490
ABOVE 2112" TO 2160"	± 0.500
ABOVE 2160" TO 2208"	± 0.510
ABOVE 2208" TO 2256"	± 0.520
ABOVE 2256" TO 2304"	± 0.530
ABOVE 2304" TO 2352"	± 0.540
ABOVE 2352" TO 2400"	± 0.550
ABOVE 2400" TO 2448"	± 0.560
ABOVE 2448" TO 2496"	± 0.570
ABOVE 2496" TO 2544"	± 0.580
ABOVE 2544" TO 2592"	± 0.590
ABOVE 2592" TO 2640"	± 0.600
ABOVE 2640" TO 2688"	± 0.610
ABOVE 2688" TO 2736"	± 0.620
ABOVE 2736" TO 2784"	± 0.630
ABOVE 2784" TO 2832"	± 0.640
ABOVE 2832" TO 2880"	± 0.650
ABOVE 2880" TO 2928"	± 0.660
ABOVE 2928" TO 2976"	± 0.670
ABOVE 2976" TO 3024"	± 0.680
ABOVE 3024" TO 3072"	± 0.690
ABOVE 3072" TO 3120"	± 0.700
ABOVE 3120" TO 3168"	± 0.710
ABOVE 3168" TO 3216"	± 0.720
ABOVE 3216" TO 3264"	± 0.730
ABOVE 3264" TO 3312"	± 0.740
ABOVE 3312" TO 3360"	± 0.750
ABOVE 3360" TO 3408"	± 0.760
ABOVE 3408" TO 3456"	± 0.770
ABOVE 3456" TO 3504"	± 0.780
ABOVE 3504" TO 3552"	± 0.790
ABOVE 3552" TO 3600"	± 0.800
ABOVE 3600" TO 3648"	± 0.810
ABOVE 3648" TO 3696"	± 0.820
ABOVE 3696" TO 3744"	± 0.830
ABOVE 3744" TO 3792"	± 0.840
ABOVE 3792" TO 3840"	± 0.850
ABOVE 3840" TO 3888"	± 0.860
ABOVE 3888" TO 3936"	± 0.870
ABOVE 3936" TO 3984"	± 0.880
ABOVE 3984" TO 4032"	± 0.890
ABOVE 4032" TO 4080"	± 0.900
ABOVE 4080" TO 4128"	± 0.910
ABOVE 4128" TO 4176"	± 0.920
ABOVE 4176" TO 4224"	± 0.930
ABOVE 4224" TO 4272"	± 0.940
ABOVE 4272" TO 4320"	± 0.950
ABOVE 4320" TO 4368"	± 0.960
ABOVE 4368" TO 4416"	± 0.970
ABOVE 4416" TO 4464"	± 0.980
ABOVE 4464" TO 4512"	± 0.990
ABOVE 4512" TO 4560"	± 1.000

CODE LETTERS H 41
HOOD. (USED TO
IDENTIFY STOPS ON JIS)

1
V. COMPANY, 8-8-44

TYPES (B) AND (C)

2
V. COMPANY, 11-7-44