



BY-PASSING

3	+225 To 0	2.2μf
4	+150 To 0	5.5μf
5	+110 To 0	2.2μf
6	+50 To 0	0.1μf
7	+20 To 0	0.1μf
8		
9	-130 To 0	0.1μf
10	110	
11	110 AC	
12	0-GROUND	

SA

1	INPUT
2	INPUT
3	INPUT
4	INPUT
5	INPUT
6	INPUT
7	INPUT
8	INPUT
9	INPUT
10	INPUT
11	INPUT
12	GROUND

PC

3	+225
4	+150
5	+110
6	+50
7	+20
8	
9	-130
10	110 AC
11	110
12	0-GROUND

- 1
- 2
- 3
- 5
- SB
- | | |
|----|-------------|
| 1 | OUTPUT |
| 2 | OUTPUT |
| 3 | OUTPUT |
| 4 | OUTPUT |
| 5 | OUTPUT |
| 6 | OUTPUT |
| 7 | OUTPUT |
| 8 | OUTPUT |
| 9 | OUTPUT |
| 10 | OUTPUT |
| 11 | P.M. OUTPUT |
| 12 | GROUND |

REVISIONS

LOCATION NUMBERS ADDED.

15K RESISTORS ADDED ON +150 VOLTAGES.

1

BY-PASSING ADDED.

2

OF CL. TIC. E.

TY OF PEN. IM.

PULSE AMPLIFIER

CJM-C

OCT. 24, 1945

Y.P.E.B.

PX-4-116