



- SOCKET "D" INPUT SOCKET (JONES C412AB)
- 1 +225
  - 2 +150
  - 3 +110
  - 4 +75
  - 5 +50
  - 6 +20
  - 7 0
  - 8 -40
  - 9 -85
  - 10 -130
  - 11 AC 110V Hot
  - 12 AC 110V NEUTRAL

THESE 5 TO BE MOUNTED IN PUNCH BELOW OUTPUT SOCKETS (1-10)

- NOTES:
- ALL RESISTORS UNLESS OTHERWISE SPECIFIED ARE:
    - A. RATED AT 1/2 WATT
    - B. WITHIN ± 10% OF THE STATED VALUE.
  - ALL CONDENSERS UNLESS OTHERWISE SPECIFIED ARE:
    - A. BARELINE MULLER MICA CORED 50V
    - B. WITHIN ± 20% OF THE STATED VALUE
  - SOCKET "A" & "C" SHALL BE MOUNTED TO FIT PLUGS ON DECADE TURN IN UNIT SEE DRAWING NO. EX-101

RESISTOR & CONDENSER CO MARKED ARE TAKEN FROM ONE OF THE FOLLOWING FOUR GROUPS FOR ANY GIVEN UNIT.

GROUP	RESISTOR	COND. GRK
1	- 10%	+ 20%
2	+ 5%	+ 10%
3	- 5%	+ 10%
4	+ 10%	- 10%

TEN-STAGE STEPPER

ENIAC & COMPUTING LABORATORY

DATE: C-10-47. Des: *Manlygn* App: *[Signature]*

PX-4-122